

KIO RTLS Server

Technical Specifications



Model	SuperMicro SuperServer E100-9AP
CPU	7th Generation Intel® Core i7-7600U Processor
RAM	4GB
Input/Output	1 USB 3.1 (Type C), 2 USB 3.0, 4 USB 2.0
Power Supply	12V DC 60W power adapter
Form Factor	3.5" SBC, wall mountable
IP Class	IP51
Communication Links	One 1 Gbps Ethernet port for client network, One 1 Gbps Ethernet port for the Anchors network and integrated Wi-Fi interface for the Anchors network
Technical Spec	www.supermicro.com/products/system/Box_PC/SYS-E100-9S.cfm

Optional Switches for the Power over Ethernet Setup



Producer	TG-NET
Model	PS6081_120 / P1009D-8POE
10/100base-tx (rj45) ports	9 (8 + 1 upstream port for the server)
PoE Ports	8
Technical specifications	www.tg-net.net



Producer	TP-Link
Model	TL-SF1005P
PoE Port Power Capability	Up to 15.4W for each PoE port
10base-t / 100base-tx	5 (4 + 1 upstream port for the server)
PoE Ports	4
Dimensions	99.8 x 98 x 25 mm
IP Class	IP51
Technical specifications	www.tp-link.com

The specifications are subject to change without notice.

